

ADAM-4016

ADAM-4017

1-ch Analog Input/Output Module

8-ch Analog Input Module

- 1 Motion Control
- 2 Hazardous Location
- 3 Energy Automation
- 4 Building Automation Systems
- 5 Automation Software
- 6 Operator Panels
- 7 Automation Panel PCs
- 8 Industrial Monitors
- 9 Industrial Ethernet
- 10 Device Servers & Gateways
- 11 Serial Communication Cards
- 12 Embedded Auto. Computers
- 13 PACs
- 14 M2M I/O
- 15 Distributed Nano Controllers
- 16 RS-485 I/O
- 17 Ethernet I/O
- 18 DAO Boards



ADAM-4016



Specifications

General

- **Connectors** 2 x plug-in terminal blocks (#14 ~ 22 AWG)
- **Power Consumption** 2.2 W @ 24 V_{DC}
- **Watchdog Timer** System (1.6 s)
- **Supported Protocols** ASCII command

Analog Input

- **Channels** 1 differential
- **Input Impedance** Voltage: 2 M Ω
Current: 125 Ω (Added by users)
- **Input Type** mV, V, mA
- **Input Range** ± 15 mV, ± 50 mV, ± 100 mV, ± 500 mV, ± 20 mA

Analog Output

- **Channels** 1
- **Accuracy** 0.05% of FSR
- **Output Type** V
- **Output Range** 0 ~ 10 V
- **Drift** ± 50 ppm/ $^{\circ}$ C
- **Drive Current** 30 mA
- **Isolation Voltage** 3,000 V_{DC}

Digital Output

- **Channels** 4, open collector to 30 V, 30 mA max. load
- **Power Dissipation** 300 mW

Common Specifications

General

- **Power Input** Unregulated 10 ~ 30 V_{DC}
- **Connectors** 2 x plug-in terminal block (#14 ~ 22 AWG)

Analog Input

- **Accuracy** Voltage mode: $\pm 0.1\%$ or better
Current mode: $\pm 0.2\%$ or better
- **Resolution** 16-bit

- **Sampling Rate** 10 sample/second (total)
- **Isolation Voltage** 3,000 V_{DC}
- **CMR @ 50/60 Hz** 120 dB
- **NMR @ 50/60 Hz** 100 dB
- **Span Drift** ± 25 ppm/ $^{\circ}$ C
- **Zero Drift** ± 6 μ V/ $^{\circ}$ C

Environment

- **Humidity** 5 ~ 95% RH
- **Operating Temp.** -10 ~ 70 $^{\circ}$ C (14 ~ 158 $^{\circ}$ F)
- **Storage Temp.** -25 ~ 85 $^{\circ}$ C (-13 ~ 185 $^{\circ}$ F)



ADAM-4017



Specifications

General

- **Power Consumption** 1.2 W @ 24 V_{DC}
- **Watchdog Timer** System (1.6 second)
- **Supported Protocols** ASCII command

Analog Input

- **Channels** 6 differential and 2 single-ended
- **Input Type** mV, V, mA
- **Input Range** ± 150 mV, ± 500 mV, ± 1 V, ± 5 V, ± 10 V, ± 20 mA

Ordering Information

- **ADAM-4016** 1-ch Analog Input/Output Module
- **ADAM-4017** 8-ch Analog Input Module